

Brief Description:

Peel Ply is used to build up a textured surface for a better bonding or painting after it is removed from the final composite material.

Technical Data:

PEEL PLY	Base Polymer	Color / Pilot Yarn	Thread size	Thickness	Area weight	Tensile strength	Warp / Weft density	Temperature resistance
			dtex	mm	g/m ²	N/cm	1/cm	°C
PA 6.6 85 g/m ²	PA 6.6	Red	210	0.15	85	315	19/15	200
PA 6.6 105 g/m ²	PA 6.6	Black	210	0.19	105	350	20/20	200
PA 6.6 153 g/m ²	PA 6.6	Black	420	0.15	153	450	17/16	200
PA 6 85 g/m ²	PA 6	Red	210	0.15	85	310	17/17	160
Green 85 g/m ²	PA 6.6	Plain green	210	0.15	85	315	18/16	200
PA 6.6 60 g/m ²	PA 6.6	Plain white	40	0.05	60	645	72/46	180
PA 6.6 60 g/m ² Adhesive coating	PA 6.6	Plain white	40	0.3	60	645	72/46	180
PA 6.6 85 g/m ² Adhesive coating	PA 6.6	Red	210	0.15	85	315	19/15	200

Additional Information:

Delivery form	Rolls with 200 m
Width	25 - 1550 mm
Fabric weave	Plain
Treatment	Washed, heat setting

Hazard Information: Store tightly closed and in a cool, well-ventilated area. Protect from humidity and direct sunlight. Detailed information in material safety data sheet.



The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Lehmann & Voss & Co. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.

Lehmann&Voss&Co.
Alsterufer 19
20354 Hamburg
E-Mail: info@lehvoss.de
Internet: www.lehvoss.de

Contact:
Sales LUVATOL
Phone: +49/40/44 19 7 - 475
Fax: +49/40/44 19 7 - 478
luvaton@lehvoss.de

Lehmann&Voss&Co. 