

Brief Description:

Peel Ply is used to build up a textured surface for a better bonding or painting after it is removed from the final composite material.

Technical Data:

PEEL PLY *	Fibre type (warp / weft)	Color / Pilot Yarn	Thread size (warp)	Thickness	Area weight	Tensile strength	Warp / Weft density	Temperature resistance
			dtex	mm	g/m ²	N/cm	1/cm	°C
PA 6.6 85 g/m ²	PA 6.6 / PET	Red	210	0.15	85	315	19/15	200
PA 6.6 105 g/m ²	PA 6.6 / PET	Black	210	0.19	105	350	20/20	200
PET 85 g/m ²	PET / PET	Red	210	0.15	93	270	17/15	180
PA 6 85 g/m ²	PA 6 / PET	Red	210	0.15	85	240	18/15	180
PA 6 P 85 g/m ²	PA 6 / PA 6	Red	210	0.15	83	290	18/16	180
Green 85 g/m ²	PA 6.6 / PET	Plain green	210	0.15	85	315	18/16	200
AC PA 6.6 85 g/m ² Adhesive coating	PA 6.6 / PET	Red	210	0.15	85	315	18/16	200

Additional Information:

Delivery form	Rolls with 200 m
Width	25 - 1550 mm
Fabric weave	Plain
Treatment	Washed, heat setting

* Product selection. Other types on request

Hazard Information: Store tightly closed and in a cool, well-ventilated area. Protect from humidity and direct sunlight. Detailed information in material safety data sheet.



The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Lehmann & Voss & Co. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.

Lehmann&Voss&Co.
Alsterufer 19
20354 Hamburg
E-Mail: info@lehvoss.de
Internet: www.lehvoss.de

Contact:
Sales LUVATOL
Phone: +49/40/44 19 7 - 475
Fax: +49/40/44 19 7 - 478
luvaton@lehvoss.de

Lehmann&Voss&Co.